STICKER INSTRUCTIONS



6h of Barcelona

MANDATORY STICKER INSTRUCTIONS FOR 6H OF BARCELONA 2025:

- » Stickers will be handed over on THU FRI before the Winter Series racing days
- » To print Pirelli logo directly on racing suit please contact: <u>marco.Soana@pirelli.com</u> / <u>emilia.capasso@pirelli.com</u>
- » MANDATORY stickers: Failing stickers or invalid placing of stickers may lead to not passing scrutineering
- » Standard starting numbers are available on site at the Organiser's office. Maximum sizes: See legend below
- » In case you want to print the stickers already in your workshop find the files and instructions here (Not mandatory, stickers will be provided by Gedlich on site): https://winter-series.com/downloads/2025-WS-6h-Barcelona-Sticker.zip



STICKER I FGEND

STICKER ELGEND				
NR.	AMT.	TYPE	POSITION	SIZE (WxH in MM)
1	4x	Pirelli sticker	Front and rear bumper, left + right	280 x 80
2	2x	Starting number plates	Front section of doors, left + right	400 x 330
3	2x	Alpha Live (or similar)	Rear quarter panel above rear wheel left + right	-
4	2x	6h of Barcelona mirror sticker	Wing mirrors left + right: Facing forward	W = 112
5	1x	Lumirank system	Passenger side of windshield. Directly under window banner (read info on page 2)	-
6	1x	6h of Barcelona window banner	Windshield (may be cut in to fit above tear-offs)	1385 x 185
7	1x	Classification sticker (Only GT3)	Rear bumper 2/3 rd right section (Only GT3 cars)	240 x 80
8	1x	Starting number small	Rear bumper, next to classification sticker	H = 80
9	2x	Pirelli racing suit logo	Chest: left side, sleeve: right side	W = 100
10	1x	6h Portimão racing suit logo	Chest: left or right side (not mandatory)	W = 80
	17x			

STICKER INSTRUCTIONS 6h of Barcelona



INSTALLATION INSIDE THE CAR:

The display must be mounted inside the car underneath the windshield banner only by using the support installation set (picture A). A Lumirank system that is too close close or partially under the windshield banner or edge of the windscreen is not accepted.

OPTIONAL REQUIREMENTS

The display should be attached along the edge with clear Helitape or with the anti-glare tape included in the installation kit. Bonding with any other tapes like for instance Tesa or Gaffa is not allowed (Picture B)!

It is important to make sure that all LEDs of the display are clearly visible with a 20 mm gap around all edges. This is to ensure the information can be read clearly during the race. Covered LEDs, due to decals will not be acceptable (Picture C).

Make sure to use the originally provided mounting kit as explained and maintained in good condition. Replacement velcro strips are available for both the panel and windscreen sides. The use of other Velcro Type is not acceptable (Picture E).

ELECTRIC FUNCTION

The display is connected correctly when the blue LED (Power) is glowing permanently after switching Main "on" (Picture D) and a green LED (Active) flashes at the same time. The two LEDs are located at the top center next to the small serial number sticker.

IMPORTANT NOTICE: The display needs to stay on during pit stops. This is necessary for vehicles with Power Box. The display is switched on with "Main Switch ON".













